



CONFIDENTIAL & PROPRIETARY INFORMATION

This document contains Confidential and Proprietary Information of Alliance LLC, and all design, manufacturing, reproduction, use, and sale rights of such information are expressly reserved

ALL DIMENSIONS ARE IN MM (INCH)

**NOTES:**

- MAGNET PROPERTIES PER N-33SH:
Br: 11,400-11,700 G
Hc: 10,700-11,700 Oe
Hci: ≥20,000 Oe
T max: 150 C
- SUPPLIED MAGNETIZED THROUGH THE THICKNESS
- PARTS ARE NICKEL PLATED FOR 15hrs SALT SPRAY MIN.



REV	DESCRIPTION	DATE	BY

TOLERANCES (UNLESS OTHERWISE NOTED)	
DECIMAL	METRIC
X.XX = ± .01	X.X = ± .25
X.XXX = ± .005	X.XX = ± .13
ANGLES ± .5°	
DO NOT SCALE DRAWING	

Alliance LLC 1450 CLARK DRIVE, VALPARAISO, INDIANA 46385		
DESCRIPTION: 2 mm x 2 mm DISC MAGNET		
SENSOR MAGNET		P/N: ALC2020X
GRADE: N-33SH	Drwg by: BT	REV LEVEL: A
COATING: Nickel	Appr by: DV	Approval: 03-13-2023